



## RSK50

RSK50 Işıklık Sistemi, Kapaklı, yarı kapaklı ve silikon ışıklık sistemlerinden oluşmaktadır. Profil genişliği 50 mm olup 1,8 mm et kalınlığı bulunmaktadır. Çelik takviyeli profiller kullanılarak ışıklık sisteminin yapılmasına imkan verilir. Kertmesiz düşey ve yatay profil bağlantı çözümü sunar. 8 mm+16 mm+5/5 mm ve 8 mm+16 mm+6/6 mm ısıcam alternatifleri bulunur. Fitilden su tahliye sistemi vardır. Yüksek ısı yalıtım değerleri ile öne çıkmaktadır.

RSK50 Skylight System is comprised of and structural glazing skylight systems. There is a profile width of 50mm and Wall thickness of 1,8mm. By using steel reinforced profiles, it is enabled to produce the skylight system. It provides a unnotched vertical and horizontal profile connection solution. 8mm + 16mm + 5/5mm and 8mm + 16mm + 6/6mm double-glazing alternatives are available. There is a water discharge system through the cord. It becomes prominent with its high heat insulation values.

# İŞIKLIK SİSTEMİ SKYLIGHT SYSTEM

## Teknik Özellikleri / Technical Properties

Profil Geniřliđi / Profile Width	50 mm
Profil Et Kalınlıđı / Wall Thickness	1,8 mm
Max Cam Kalınlıđı / Max. Glass Thickness	37 mm

## Kullanım Seçenekleri / Application Options

Kapaklı Cephe / Facade With Cap	*
Silikon Cephe / Structural Glazing	*
Yarı Kapaklı Cephe / Two Side	*
Dıřa Açılır Gizli Kanat / Outward Opening Hidden Vent	*
Çelik Takviyeli Sistem / Steel Reinforcement System	*

## Performans Deđerleri / Performance Values

Sistem Uf Deđerı - EN 10077 - 2 (Thermal Insulation Value)

